

1 Clifford A. Chanler, State Bar No. 135534  
 2 Jenny Cohn, State Bar No. 169973  
 3 CHANLER & ASSOCIATES  
 4 1700 Montgomery Street, Suite 110  
 5 San Francisco, CA 94111  
 6 (415) 391-1122

**FILED**

JUN 28 1995  
*M. Louren*  
 HOWARD HANSON  
 MARIN COUNTY CLERK  
 By M. Louren, Deputy

7 Attorneys for Plaintiff  
 8 AS YOU SOW

SUPERIOR COURT OF THE STATE OF CALIFORNIA

IN AND FOR THE COUNTY OF MARIN

9 AS YOU SOW, a non-profit  
 10 organization,

No. 164440

11 Plaintiff,

12 v.

STIPULATION FOR  
ENTRY OF JUDGMENT

13 DYMON, INC.,

14 Defendant,

15 \_\_\_\_\_  
 16  
 17  
 18 IT IS HEREBY STIPULATED, by and between plaintiff As  
 19 You Sow and defendant Dymon, Inc., through their respective  
 20 representatives, that judgment in the above-entitled action be  
 21 entered in accordance with the terms of the settlement  
 22 agreement between the parties, which is attached hereto as  
 23 Exhibit A.

24 Dated: June 21, 1995

by: *Jenny Cohn*  
 \_\_\_\_\_  
 Jenny Cohn  
 Attorney for Plaintiff  
 AS YOU SOW

27 Dated: June 8, 1995

by: *Hibberd V.B. Kline, III*  
 \_\_\_\_\_  
 Hibberd V.B. Kline, III  
 Attorney for Defendant  
 DYMON, INC.

00339800 06/28/95CLRK\* 182.00

8

# **Exhibit A**

## SETTLEMENT AGREEMENT

On June 16, 1995 in San Francisco, California, As You Sow ("AYS") and Dymon Inc., ("Dymon") agreed to the following terms and conditions:

### **WHEREAS:**

AYS is a not-for-profit public interest foundation dedicated to promoting consumer awareness, protecting the environment and improving human health; and

On April 1, 1988, the State of California officially listed methylene chloride and perchloroethylene as chemicals known to cause cancer, pursuant to Health & Safety Code §25249.8; and

On January 1, 1991, the State of California officially listed toluene as a chemical known to cause birth defects or other reproductive harm, pursuant to Health & Safety Code §25249.8; and

Dymon is a corporation headquartered in Kansas City, Kansas, that manufactures certain cleaning and maintenance products, the vast majority of which are for distribution and use exclusively outside the State of California, but some of which are for distribution and use within the State of California, (all such cleaning and maintenance products, both for distribution and use within and without the State of California, being collectively referred to as the "Products"); and

Some of the Products contain toluene, methylene chloride and perchloroethylene. A list, identified by product number, of the specific Products that contain Proposition 65-listed chemicals and are covered by this Agreement is attached as in Exhibit A and incorporated herein by reference; and

Dymon manufactures no products for distribution and use in the State of California which contain benzene, chromium, lead and lead components, or crystalline silica; and

Certain of the Products listed in Exhibit A have been distributed and sold by Dymon for use in California since April 1, 1989; and

On February 9, 1995, AYS served Dymon with a document entitled "60-Day Notice" which provided Dymon with notice that it was allegedly in violation of Health & Safety Code §25249.6 for failing to warn purchasers that certain products it manufactures expose users in California to Proposition 65-listed chemicals; and

Shortly after receiving the 60-Day Notice of Proposition 65 violation, Dymon modified its labels for the Products, so that these

labels now provide a clear and reasonable warning within the safe harbor provisions of Health & Safety Code § 25249.6 and California Administrative Code, Title 22, § 12601.

**NOW, THEREFORE, THE PARTIES AGREE AS FOLLOWS:**

1. **Warnings.** Dymon agrees that as of April 30, 1995, it shall not ship (or cause to be shipped) any of the Products for sale or use in the State of California unless each such Product contains one of the following warning statement(s) on its label:

For Products containing listed carcinogens:

**"WARNING: This product contains a chemical(s) known to the State of California to cause cancer."**

For Products containing listed reproductive toxins:

**"WARNING: This product contains a chemical(s) known to the State of California to cause birth defects or other reproductive harm."**

The parties agree that the sample labels attached hereto as Exhibit B satisfy this requirement.

2. **Restitution and Costs.** Upon execution of this Settlement Agreement, Dymon agrees to pay \$9,500.00 to AYS. The restitutionary component of this payment, which is made pursuant to Business & Professions Code §17203, shall be made to the AYS Proposition 65 Investigation Fund. The cost component of this payment will be used by AYS to help defray its investigation fees and costs, expert fees, reasonable attorneys' fees, and any other costs incurred as a result of investigating, bringing this matter to Dymon's attention and negotiating a settlement in the public interest.

3. **AYS Release.** AYS, in consideration of the payments set forth herein, on behalf of itself and the public interest, pursuant to Health & Safety Code § 25249.7 and Business & Professional Code § 17204, and its attorneys, employees, successors, assigns, predecessors, subrogees, principals, agents, consultants and insurers, does hereby release and forever discharge Dymon (and all in Dymon's chain of distribution, including but not limited to all distributors, wholesalers and retailers) and the successors, assigns, predecessors, stockholders, officers, directors, subrogees, subsidiaries, trustees, corporate parents, affiliates, board members, agents, attorneys, employees and consultants, of each of them of and from any and all claims, demands, actions, causes of action, duties, debts, sums of money, suits, reckonings, contracts, controversies, agreements, promises, damages, responsibilities, obligations, liabilities and accounts of whatsoever kind, nature or

description, direct or indirect, at law or in equity, in contract or tort or otherwise arising from or relating to any facts or legal theories involving toluene, methylene chloride, or perchloroethylene in the Products and Proposition 65, it being the specific intent and purpose of the parties hereto that this settlement agreement and release shall extend to any and all persons, corporations, associations, or other entities and to any and all of the matters aforesaid, whether now known or unknown, which exist or might be claimed to exist at, prior to, or after the date hereof relating to exposure to toluene, methylene chloride, or perchloroethylene in the Products, and AYS on behalf of itself and the public interest, its attorneys, employees, successors, assigns, predecessors, subrogees, principals, agents, consultants and insurers, and each of them, expressly waive, release and relinquish any and all claims or rights to assert that any such matter, cause or thing of any kind or nature whatsoever has been, through oversight or error or intentionally or unintentionally, omitted with respect to exposure to toluene, methylene chloride, or perchloroethylene in the Products.

4. **Dymon Release.** Dymon, in consideration of the commitments set forth herein, on behalf of itself, its attorneys, employees, successors, assigns, predecessors, subrogees, principals, agents, consultants and insurers, does hereby release and forever discharge AYS, its successors, assigns, predecessors, stockholders, officers, directors, subrogees, subsidiaries, trustees, corporate parents, affiliates, board members, agents, attorneys, employees and consultants, of and from any and all claims, demands, actions, causes of action, duties, debts, sums of money, suits, reckonings, contracts, controversies, agreements, promises, damages, responsibilities, obligations, liabilities and accounts of whatsoever kind, nature or description, direct or indirect, at law or in equity, in contract or tort or otherwise arising out of or relating, directly or indirectly, to the application of Proposition 65 to toluene, methylene chloride, or perchloroethylene in the Products, or arising from or relating to any facts or legal theories involving the application of Proposition 65 to the exposure to toluene, methylene chloride, or perchloroethylene in the Products, it being the specific intent and purpose of the parties hereto that this settlement agreement and release shall extend to any and all persons, corporations, associations, or other entities and to any and all of the matters aforesaid, whether now known or unknown, which exist or might be claimed to exist at, prior to, or after the date hereof, and Dymon, its attorneys, employees, successors, assigns, predecessors, subrogees, principals, agents, consultants and insurers, and each of them, expressly waive, release and relinquish any and all claims or rights to assert that any such matter, cause or thing of any kind or nature whatsoever has been, through oversight or error or intentionally or unintentionally, omitted with respect to the application of Proposition 65 to the exposure to toluene, methylene chloride, or perchloroethylene in the Products.

5. **MSDS Warnings.** Dymon shall ensure that the Material Safety Data Sheets ("MSDS") for each of the Products contains a warning that will be substantially consistent in wording with the on-label warning language required by paragraph 1. The parties hereto agree that the MSDS's attached hereto as Exhibit C satisfy this requirement.

6. **Stipulated Judgment.** The parties shall file a stipulated judgment to be approved pursuant to CCP § 664.6 by the San Francisco Superior Court in accordance with the terms of this Agreement.

7. **Severability.** In the event that any of the provisions of this Agreement are held by a Court to be unenforceable, the validity of the enforceable provisions shall not be adversely affected.

8. **Attorneys' Fees.** In the event that a dispute arises with respect to any provision(s) of this Agreement, the prevailing party shall be entitled to recover costs and reasonable attorneys' fees.

9. **Governing Law.** The terms of this Agreement shall be governed by the laws of the State of California.

10. **Notices.** All correspondence to AYS shall be mailed to:

Jennifer S. Cohn, Esq.  
Chanler & Associates  
1700 Montgomery Street  
Suite 110  
San Francisco, CA 94111

All correspondence to Dymon shall be mailed to:

Dymon, Inc.

c/o Blackwell, Sanders, Matheny, Weary &  
Lombardi L.C.  
Two Pershing Square  
2300 Main Street, Suite 1100  
P.O. Box 419777  
Kansas City, MO 64141-6777


Attn: Hibberd V. B. Kline, III, Esq.

11. **No Admissions.** Nothing in this Agreement shall be construed as an admission by Dymon of any fact, finding, issue of law, or violation of law, nor shall compliance with this Agreement constitute or be construed as an admission by Dymon of any fact, finding, conclusion, issue of law, or violation of law. However, this paragraph shall not diminish or otherwise affect the obligation, responsibilities, and duties of Dymon under this Agreement.

12. **Authorization.** The undersigned are authorized to execute this Agreement on behalf of their respective parties and have read, understand and agree to all of the terms and conditions of this Agreement.

AGREED TO:

AS YOU SOW

  
\_\_\_\_\_


Printed Name

\_\_\_\_\_

Title

AGREED TO:

DYMON, INC.

  
\_\_\_\_\_

DONALD L. CODA  
Printed Name

EXECUTIVE VICE PRESIDENT  
Title

EXHIBIT A



## DYMON PRODUCTS REQUIRING PROP 65 WARNINGS

Product No.	California Distribution	Toluene Warning	Methylene Chloride Warning	Perchloroethylene Warning
A-044		X		
A-072		X		
A-073		X		
A-078	X	X		
A-082	X		X	
A-086			X	
A-089			X	
A-091		X	X	
A-093		X		
A-095				X
A-097			X	X
A-098				X
A-104	X	X		
A-105			X	
A-112			X	
A-116		X		
A-122		X		
A-143			X	
A-158				X
A-159	X			X
A-162			X	X
A-206				X
A-218			X	X
A-248			X	
A-284		X		
A-286		X	X	
A-303			X	
A-304		X		
A-353		X	X	
A-369			X	
A-381			X	
A-383			X	
A-397		X		
A-401			X	X
A-402			X	X
A-403			X	X
A-404			X	X
A-511			X	X
A-547			X	X

Product No.	California Distribution	Toluene Warning	Methylene Chloride Warning	Perchloroethylene Warning
A-580		X		
A-811			X	
A-817			X	
A-821			X	
A-825			X	X
A-826			X	
A-828			X	
A-849			X	
A-865			X	
A-874			X	
A-889			X	X
B-027			X	X
B-029		X	X	
B-032			X	
B-037		X		
B-043		X		
B-045A		X		
B-078		X		
B-082		X		
B-086			X	
B-091		X	X	
B-097			X	
B-104		X		
B-122		X		
B-158				X
B-205				X
B-215		X		
B-238				X
B-253			X	
B-286		X		
B-353		X	X	
B-401			X	X
B-402			X	X
B-624		X		
B-667			X	
B-668			X	
B-669			X	

EXHIBIT B

[Sample Labels for Products]

R-1  
JCO



Dymon®  
The new idea company.™

**SHAKE WELL BEFORE USING**

**USE ON:** • Washroom Walls • Public Buildings • Bridges • Signs  
Buses • Sidewalks • Fences • Trucks

**DIRECTIONS FOR USE:** Spray onto marks. Wait 5-10 minutes. Remove with clean cloth. If stubborn, repeat application. Allow to stand 30 to 60 minutes. If accumulation is heavy, remove with spatula, then re-spray. If extreme stubbornness is encountered, use stiff bristle brush and work into the stain. Spray on again - wipe off again. Use clean brush or cloth.

This product may be used on many surfaces: fiberglass, brick, concrete, marble, ceramic tile, aluminum, steel, brass, glass, chrome, enamels, varnishes, porcelain, formica and baked enamel. Care should be exercised when used on synthetic surfaces which are susceptible to solvent damage (asphalt tile, rubber, some paints and some plastics). Not recommended on flat or semi-gloss painted surfaces. Pretest in hidden area if uncertain. **DANGER. Corrosive.** Do not get in eyes, on skin or clothing. Do not use around ignition sources such as heat, sparks, open flame, etc. Do not swallow. Do not inhale mist or vapors. Use with adequate ventilation. Contents under pressure. Do not puncture or incinerate container. Store in a cool (under 120°F) dry location away from heat, sparks, open flame or direct sunlight. Direct spray away from face. Replace cap when not in use. Do not deliberately concentrate and inhale vapors. **WARNING:** This product contains a chemical (Toluene) known to the State of California to cause birth defects or other reproductive harm.

**FIRST AID: EYES**—Flush with plenty of water for at least 15 minutes. Get medical attention immediately. **INGESTION**— Call a physician immediately. ONLY induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person. **INHALATION**—Get to fresh air. If breathing has stopped, qualified personnel should administer artificial respiration. **SKIN**—Flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately. **READ THE MATERIAL SAFETY DATA SHEET (MSDS) BEFORE USING THIS PRODUCT.**

**HMIS RATING:** Health - 3; Flammability - 2; Reactivity - 0; Personal Protection - B.  
**CONTAINS (CAS No.):** Toluene (108-88-3); Isobutane (75-28-5); 2-Butoxyethanol (111-76-2); Propane (74-98-6); Acetone (67-64-1); 9-Octadecenoic acid (112-80-1); and Water (7732-18-5).

This product contains 542 grams per liter VOC's  
Authorized by U.S.D.A. for use in federally inspected meat and poultry plants  
For Commercial/Industrial Use Only. DA-078



Dymon®  
The new idea company.™


MANUFACTURED BY:  
DYMON, INC.  
3401 KANSAS AVENUE  
KANSAS CITY, KANSAS 66106  
(913) 321-5537

# VANDAL MARK REMOVER

## REMOVES:

**Crayon • Pencil • Lipstick  
Mimeo Ink • Masking Tape  
Ball Point Inks • Spray Paint**

*New Jelled Formulation  
Will Not Run Off*



Net Wt. 14 oz (397 g)

**DANGER**

Flammable liquid and vapor. Corrosive. Causes eye and skin burns. May be harmful or fatal if swallowed. May cause respiratory tract irritation. May be absorbed through intact skin. Contents under pressure.



Font List  
.....  
Helvetica  
  
Avant Garde  
  
Zapl Dingbats  
  
Graphic List  
.....  
Dymon Logo  
  
prg-06.eps  
  
2.0ps

▲ INSTITUTIONAL ▲ INDUSTRIAL ▲ COMMERCIAL ▲ AUTOMOTIVE ▲ INSTITUTIONAL

DA078P16 Poly  
DYMON/POLY 4260  
4/05/95 Christi

4/92



Dymon®

The new idea company.™

Polishes  
Cleans  
Dusts

# Dustmop & Cloth



# Treatment

Net Wt. 17 oz (1 lb 1 oz) (482 g)

KEEP OUT OF REACH OF CHILDREN  
WARNING

Flammable liquid and vapor.  
Contains petroleum distillates.  
Causes eye and skin irritation.  
May be harmful if inhaled or swallowed.  
Contents under pressure.

Makes dusting easier - prevents germ filled  
dust from scattering - reduces dusting time.

### DIRECTIONS

#### Shake Well Before Using

Remove cap - hold can 6-8 inches from dust mop or spray cloth and spray lightly over entire mop or dust cloth. Dust in regular way. Apply spray to dust cloth or mop as often as needed - at least once a week. Dust cloths or mops sprayed with this product convert dust into heavy lint which shakes neatly into a newspaper or wastepaper basket. No annoyance from flying dust.

Use on dust cloths — picks up dust like a magnet - prevents dust from scattering. Spray on air conditioning filters after cleaning. Holds dust and pollen on filters - prevents dust and pollen from entering the room.

### USE ON

Furniture, venetian blinds, radiators, woodwork, wood floors, window frames and sills, autos and other surfaces where dust gathers.

### WARNING

Contains petroleum distillates. Flammable liquid and vapor. Do not use around ignition sources such as heat, sparks and open flame. Do not smoke while using. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Remove and wash contaminated clothing before reuse. Avoid inhaling mist or vapors. Use with adequate ventilation. Do not swallow. Contents under pressure. Do not puncture or incinerate container. Store in a cool (under 120°F) dry location away from heat, sparks, open flame, and direct sunlight. Direct spray away from face. Replace cap when not in use. Do not deliberately concentrate and inhale vapors. WARNING: This product contains a chemical (methylene chloride) known to the State of California to cause cancer.

Note: This product is not intended for floor maintenance. Overspray onto the floor may present a slip hazard. Remove promptly.

FIRST AID: Eyes - Flush with plenty of water for at least 15 minutes lifting eyelids to insure complete removal. Get immediate medical attention. Ingestion - Seek immediate emergency medical attention. Aspiration hazard. Only induce vomiting with a physician's direction. Inhalation - Get to fresh air. If breathing has stopped, qualified personnel should administer artificial respiration. Skin - Wash thoroughly with soap and water.

READ THE MATERIAL SAFETY DATA SHEET (MSDS) BEFORE USING THIS PRODUCT

HMS Rating: Health-1; Flammability-2; Reactivity - 0; and Personal Protection - B.

Contains (CAS No.): Methylene chloride (75-09-2); Propane (74-98-6); Mineral spirits (64742-88-7); Mineral oil (64742-55-8); and Coconut diethanolamide (120-40-1).

This product contains 507 grams per liter VOCs.

For Commercial/Industrial Use Only.

DA-082

DA082-20 DOS  
DYMON/AEROSOLS  
JOB: 4480  
4/05/95 CK



Dymon®

The new idea company.™

MANUFACTURED BY  
DYMON, INC.  
3401 KANSAS AVENUE  
KANSAS CITY, KANSAS 66105  
(913) 321-5537



RS  
Pw



# JELL DEGREASER & TAR REMOVER

New  
JELLED Formulation  
Will Not Run Off

<p><b>CLEANS</b> Gasoline &amp; Diesel Engines Metal, Concrete, Brick &amp; Stone</p> <hr/> <p><b>DISSOLVES</b> Grease, Oil Stains, Dirt, Tar and Road Oil</p>
------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Spray it on, Let it set,  
Hose it off

Net Wt. 17 oz. (1 lb. 1 oz.) (482 gms.)

**DANGER: EXTREMELY FLAMMABLE**  
**KEEP OUT OF REACH OF CHILDREN.**  
Contents under pressure.  
See side panel for additional precautions.

Authorized by U.S.D.A. for use in  
federally inspected meat and poultry plants.

**SHAKE WELL BEFORE USING**

Cleans and degreases motors on automobiles, trucks, tractors, airplanes, lawn mowers, boats, etc. Excellent for cleaning and degreasing industrial machinery, lawn and turf equipment, municipal equipment, concrete floors and driveways, boat bilges, vertical surfaces, ceilings, and hard to reach areas. Removes tar, asphalt, and grease from all types of vehicles, equipment and masonry surfaces such as brick, stone, concrete, etc. It emulsifies tar, asphalt, bitumen and asphalt based plastic cements and mono-form roofing compounds used by roofers.  
NOTE: When using this product on painted surfaces, check a small area to make sure point is not affected.

**DIRECTIONS**

1. For engines: Cover distributor and carburetor air inlet with plastic or aluminum wrap to avoid wetting.
2. Spray area to be cleaned thoroughly by pushing straight down on the valve button at the top of the can.
3. Let it set for 15 minutes or longer.
4. Hose off with strong stream of water.
5. Remove plastic or aluminum wrap. Idle engine for 15 minutes immediately after, hose off to assure complete drying.
6. For tar and asphalt, road oil, etc. removal, spray on area to be cleaned. Let it set at least 10 minutes. Agitate if necessary and hose off with water.

**DANGER:** Extremely flammable, harmful or fatal if swallowed. Contents under pressure. Do not take internally. If swallowed, DO NOT induce vomiting. Call a physician. Contains petroleum distillate. Avoid prolonged contact with skin or breathing vapor or spray mist. Use with adequate ventilation. Heat may cause bursting. Keep away from radiators and stoves. Keep out of prolonged direct sunlight. Do not puncture incinerate, or store above 120°F. **WARNING:** This product contains a chemical (Toluene) known to the State of California to cause birth defects or other reproductive harm.

READ THE MATERIAL SAFETY DATA SHEET (MSDS) BEFORE USING THIS PRODUCT  
HMIS RATINGS: Health — 1; Flammability — 4; Reactivity — 0; Personal Protection — B.  
CONTAINS (CAS No.) Toluene (108-88-3); Kerosene (8008-20-6); Mineral spirits (64742-88-7); and Propane (74-98-6).  
This product contains 732 grams per liter VOC's.

For Commercial/Industrial Use Only.



**Dymon®**  
The new idea company.™

MANUFACTURED BY  
DYMON, INC.  
3401 KANSAS AVENUE  
KANSAS CITY, KANSAS 66106  
(913) 321-5537

DA-104

DA104-20 DOS .  
DYM...AERO  
4/05/95 CK

Jan



# PENETRATING OIL & MOISTURE REMOVER



Loosens rusted nuts and bolts  
Displaces and seals out moisture  
Lubricates and penetrates  
Improves electrical properties  
Protects against rust & corrosion

Dielectric strength to 30,000 volts  
Meets Mil. Spec., C-23411  
NON FLAMMABLE

Net Wt. 18 oz (1 lb 2 oz) (510 g)

KEEP OUT OF REACH OF CHILDREN  
WARNING  
Causes eye and skin irritation.  
Harmful if inhaled or swallowed.  
May be absorbed through intact skin.  
Contents under pressure.

Authorized by U.S.D.A. for use in  
federally inspected meat and poultry plants.  
SHAKE WELL BEFORE USING

USES: Recommended for use on airplanes, automotive vehicles, farm equipment, vending machines, laundry equipment, electrical equipment, motors and windings, generators, transformers, circuit breakers, relays, controls, terminals, fuse and junction boxes, ignition systems, starter motors, distributor caps, spark plugs, alternators, multiple connections, switches and switchgear. Steel, copper, aluminum, iron, brass, painted surfaces, bronze, ceramics, tools and machinery. Freeing nuts and bolts, electrical panel board, parking meters, home workshops, outboard motors. Will not harm most plastic. Test before using. Stops and prevents corrosion, lubricates locks and hinges, snow removal equipment, refrigeration equipment. Stops corrosion on battery terminals. Displaces water and moisture with a continuous molecular film. May be applied to wet or dry surfaces. Loosens dirt, scale, and other types of corrosion. Has a lubricating effect on all moving parts, applications should be checked regularly and reapplied as conditions indicate. Never becomes dry, hard or brittle. Will not craze.

### DO NOT USE ON ELECTRONIC EQUIPMENT

DIRECTIONS: Spray liberally directly on area to be treated. Reapply periodically as required. To restore electrical equipment after total immersion: First clean the equipment. Allow the water to run off, then spray into windings, saturating all insulation and metal parts. If foaming occurs, continue to coat until foam disappears. Repeat several times if necessary.  
Warning: Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Do not swallow. Avoid inhaling mist and vapors. Store in a cool (under 120°F) dry location away from heat, sparks, open flame, and direct sunlight. Contents under pressure. Do not puncture or incinerate container. Direct spray away from face. Use with adequate ventilation. Replace cap when not in use. Do not deliberately concentrate and inhale vapors. Do not use around ignition sources such as heat, sparks, open flame, etc. WARNING: This product contains a chemical (tetrachloroethylene) known to the State of California to cause cancer. Not harmful to most plastics, but test before using. Over spray may present slip hazard.  
NOTE: Do not use on electronic equipment.  
FIRST AID: Eyes - Flush with plenty of water for 15 minutes lifting eyelids to insure complete removal. Get immediate medical attention. Ingestion - Do not induce vomiting unless under the direction of a physician. Get immediate emergency medical attention. Inhalation - Get to fresh air. If breathing has stopped, qualified personnel should administer artificial respiration. Skin - Wash thoroughly with soap and water.  
READ MATERIAL SAFETY DATA SHEET (MSDS) BEFORE USING THIS PRODUCT  
HMIS RATING: Health - 2\*; Flammability - 0; Reactivity - 0; Personal Protection - B.  
CONTAINS (CAS No.): Perchloroethylene (127-18-4); Carbon dioxide (124-38-9); Petroleum oil (mixture); 2-Butoxyethanol (111-76-2); and Perfume (Mixture)  
This product contains 11 grams/liter VOC.

For Commercial/Industrial Use Only.



DA159-20 DOS  
DYM...AERO  
4/05/95 CK

DA-159



MANUFACTURED BY:  
DYMOM, INC.  
3401 KANSAS AVENUE  
KANSAS CITY, KANSAS 68108  
(913) 321-5537

α INSTITUTIONAL α INDUSTRIAL α COMMERCIAL α AUTOMOTIVE α INDUSTRIAL

EXHIBIT C

[Sample MSDS for Products]



# Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

HEALTH  
FLAMMABILITY

HMIS®

3 REACTIVITY 0  
2 PERSONAL PROTECTION B

Identity (As Used on Label and List) A-078	Vandal Mark Remover	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
-----------------------------------------------	---------------------	-------------------------------------------------------------------------------------------------------------------------------------------------

## SECTION I

Manufacturer's Name DYMON, INC.	Emergency Telephone Number 1-800-535-5053
Address (Number, Street, City, State, and ZIP Code) 3401 KANSAS AVENUE	Telephone Number for Information 1-800-BUY-DYMON (1-800-289-3966)
P.O. BOX 6267	Date Prepared March 3, 1995
KANSAS CITY, KANSAS 66106	Signature of Preparer (Optional) REGULATORY DEPT.

## SECTION II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, Common Name(s))	CAS No.	OSHA PEL	ACGIH-TLV	Other Limits Recommended	%(Opt.)
*Acetone	67-64-1	750 ppm	750 ppm	STEL 1000 ppm	1 - 5
*2-Butoxyethanol (skin designation)	111-76-2	25 ppm	25 ppm		5 - 10
Isobutane	75-28-5	800 ppm	800 ppm		
9-Octadecenoic acid	112-80-1	None	None		
Propane	74-98-6	1000 ppm	Asphyxiant		
*Toluene	108-88-3	100 ppm	100 ppm	STEL 150 ppm	20 - 35

\* This product contains Acetone, 2-Butoxyethanol (a glycol ether compound) and Toluene that are listed and may require reporting under SARA Title III Sec. 313 if used over the threshold reporting quantity. This information must be included in all MSDSs that are copied and distributed for this material.

Any substance listed as hazardous by the States of California, Florida, Illinois, Michigan, New Jersey, Ohio, Pennsylvania or Texas is described above if known present in regulated concentrations.

## SECTION III Physical/Chemical Characteristics

Boiling Point Concentrate - initial	132° F	Specific Gravity (H <sub>2</sub> O = 1) Concentrate	0.95
Pressure (psig. @ 70° F)	40 ± 5	Melting Point	No Data
Vapor Density (AIR = 1)	Greater than one (1)	Evaporation Rate (Ethyl Ether = 1)	No Data
Solubility in Water	Complete	pH	12.5 ± 0.5

### Appearance and Odor

Opaque white to light tan emulsion with an aromatic odor in an aerosol can.

## SECTION IV - Fire and Explosion Hazard Data

USA Flame Projection Test Greater than 1/8", no flashback, Flammable	Flammable Limits	No Data	LEL No Data	UEL No Data
-------------------------------------------------------------------------	------------------	---------	----------------	----------------

### Extinguishing Media -

Carbon dioxide, dry chemical, foam.

### Special Fire Fighting Procedures -

Use water spray to keep containers cool and vapors down. Do not allow runoff to enter sewers or public watercourses. Wear self-contained breathing apparatus in chemical fires.

### Unusual Fire and Explosion Hazards -

Aerosol container (pressurized) may burst if heated over 120° F. Flammable contents.

**SECTION V - Reactivity Data**

Stability	Unstable		Conditions to Avoid - Extreme heat, direct sunlight
	Stable	X	
Incompatibility (Materials to Avoid) - Strong acids and oxidizers, chlorinated compounds and select amines.			
Hazardous Decomposition or Byproducts - Oxides of carbon, smoke, soot.			
Hazardous	May Occur		Conditions to Avoid - None known
	Will Not Occur	X	
Polymerization			

**SECTION VI - Health Hazard Data**

Route(s) of Entry	Eyes?	Inhalation?	Skin?	Ingestion?
	Yes	Yes	Yes	Yes
Health Hazards (Acute and Chronic) - Danger. Flammable liquid and vapor. Corrosive. Causes eye and skin burns. May be harmful or fatal if swallowed. May cause respiratory tract irritation. May be absorbed through intact skin. Repeated or prolonged occupational overexposure can cause dermatitis and Painter's syndrome.				
Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?	
None known	No	No	No	No

WARNING: This product contains a chemical (Toluene) known to the State of California to cause birth defects or other reproductive harm.

Signs and Symptoms of Exposure - Redness, burning, drying of skin. Drowsiness, dizziness, loss of coordination, fatigue. Slick feeling on skin. Redness, burning and tearing in eyes.

Medical Conditions Generally Aggravated by Exposure - Pre-existing skin and lung disorders. Overexposure may also aggravate pre-existing blood, liver and kidney disorders.

**Emergency and First Aid Procedures:**

Eyes - Flush with plenty of water for at least 15 minutes. Get medical attention immediately. Ingestion - Call a physician immediately. ONLY induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person. Inhalation - Get to fresh air. If breathing has stopped, qualified personnel should administer artificial respiration. Skin - Flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately.

**SECTION VII - Precautions for Safe Handling and Use**

Steps to be Taken in Case Material is Released or Spilled - Wipe up small spills with an absorbent material. For large spills, isolate traffic and ventilate area. Eliminate all ignition sources. Wear protective gear as necessary. Dike to prevent spread. Pick up on an absorbent material and put in suitable container for proper disposal. Caution, slip and fall hazard.

Waste Disposal Method - Consult local, state and federal regulations. Do not puncture or incinerate container. Replace cap on empty can, wrap, then discard container if allowed by applicable statutes.

Precautions to be Taken in Handling and Storing - Corrosive. Do not get in eyes, on skin or clothing. Do not use around ignition sources such as heat, sparks, open flame, etc. Do not swallow. Do not inhale mist or vapors. Use with adequate ventilation.

Other Precautions - Keep out of reach of children. Contents under pressure. Do not puncture or incinerate container. Store in a cool (under 120° F) dry location away from heat, sparks, open flame or direct sunlight. Direct spray away from face. Replace cap when not in use. Do not deliberately concentrate and inhale vapors.

**SECTION VIII - Control Measures**

Respiratory Protection (Specify Type) - Not usually necessary. Use with adequate ventilation. If PELs or TLVs are exceeded (see Section II), use an approved NIOSH/MSHA respirator.

Ventilation	Local Exhaust - Not usually necessary	Special - None
	Mechanical (General) - Yes	Other - None
Protective Gloves -	Eye Protection -	
Yes (impervious)	Yes (goggles or approved safety glasses)	

**Other Protective Clothing or Equipment -**

Only as needed to prevent direct contact (i.e., apron, boots, face shield, etc.)

**Work/Hygienic Practices -**

Normal. Wash thoroughly before eating, drinking, smoking, using restrooms, etc.

WARNING: The use of this product to improve the control of the named solvent, therefore, no guarantee, expressed or implied, is made as to the effects of such use or the results to be obtained if not used in accordance with directions or established safe practices. The user must assume all responsibilities, including injury or damage, resulting from its use, or its combination with other materials. The named solvent covers only that this product meets the named solvent's specifications for such product. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, AS TO DESCRIPTION, QUALITY, MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, PRODUCTIVITY, OR ANY OTHER MATTER, OF THIS PRODUCT. THE MANUFACTURER SHALL BE IN NO WAY RESPONSIBLE FOR THE PEOPLE USE OF THIS PRODUCT. The sole and exclusive remedy against the named solvent (or branch of industry) shall be reimbursement of the purchase price of the product in the amount that a reasonable condition of the product could be found to exist. NO OTHER REMEDY (INCLUDING BUT NOT LIMITED TO INCIDENTAL OR CONSEQUENTIAL DAMAGES FOR INJURY TO PERSON OR PROPERTY OR ANY OTHER INCIDENTAL OR CONSEQUENTIAL LOSS) SHALL BE AVAILABLE.

# Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

HEALTH  
FLAMMABILITY

HMIS®

1\* REACTIVITY 0  
2 PERSONAL PROTECTION B

**Identity (As Used on Label and List)**

A-082 Dustmop & Cloth Treatment

*Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.*

**SECTION I**

**Manufacturer's Name**

DYMON, INC.

**Emergency Telephone Number**

1-800-535-5053

**Address (Number, Street, City, State, and ZIP Code)**

3401 KANSAS AVENUE, P.O. BOX 6267

**Telephone Number for Information**

1-800-BUY-DYMON (1-800-289-3966)

KANSAS CITY, KANSAS 66106

**Date Prepared**

March 3, 1995

**Signature of Preparer (Optional)**

REGULATORY DEPT.

**SECTION II - Hazardous Ingredients/Identity Information**

Hazardous Components (Specific Chemical Identity; Common Name(s))	CAS No.	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED	%(Opt.)
*Methylene chloride	75-09-2	500 ppm	50 ppm		10 - 20
**Mineral spirits	64742-88-7	5mg/m3 (mist)	5mg/m3 (mist)		
**Mineral oil	64742-55-8	5mg/m3 (mist)	5mg/m3 (mist)		
Propane	74-98-6	1000 ppm	Asphyxiant		

\*Methylene chloride (syn. - Dichloromethane) is listed and may require reporting under SARA Title III Sec. 313 if used over the threshold reporting quantities. This information must be included in all MSDS's that are copied and distributed for this product. Refer to 40 CFR 372

\*\*The PEL & TLV for these chemicals is reported for mineral oil mist exposure.

Any substance listed as hazardous by the States of California, Florida, Illinois, Michigan, New Jersey, Ohio, Pennsylvania or Texas is described above if known present in regulated concentrations.

**SECTION III Physical/Chemical Characteristics**

Boiling Point Concentrate	104 ° F	Specific Gravity (H <sub>2</sub> O = 1) Concentrate	0.85
Pressure (psig. @ 70 ° F)	34 ± 5	Melting Point	No Data
Vapor Density (AIR = 1)	Greater than one (1)	Evaporation Rate (Butyl Acetate = 1)	No Data
Solubility in Water Emulsifiable		pH	Not Applicable

**Appearance and Odor -**

Clear colorless liquid with a wintergreen scent in an aerosol can.

**SECTION IV - Fire and Explosion Hazard Data**

USA Flame Projection Test 30" - Flammable	Flammable Limits No Data	LEL No Data	UEL No Data
----------------------------------------------	-----------------------------	----------------	----------------

**Extinguishing Media -**

Carbon dioxide, dry chemical, foam.

**Special Fire Fighting Procedures -**

Use water spray to keep containers cool and vapors down. Do not allow runoff to enter sewers or public watercourses. Wear self-contained breathing apparatus in chemical fires.

**Unusual Fire and Explosion Hazards -**

Aerosol container (pressurized) may burst if heated over 120 ° F.

<b>SECTION V - Reactivity Data</b>			
Stability	Unstable		Conditions to Avoid - Extreme heat, direct sunlight
	Stable	X	

**Incompatibility (Materials to Avoid) -**

Strong oxidizers, acids, alkalis, nitrogen, and reactive metals (i.e. - aluminum, potassium, sodium, etc.).

**Hazardous Decomposition or Byproducts -**

Carbon dioxide, carbon monoxide, hydrogen chloride, phosgene, ammonia, hydrogen sulfide, nitrous oxide and sulfur oxide.

Hazardous Polymerization	May Occur		Conditions to Avoid - None known
	Will Not Occur	X	

**SECTION VI - Health Hazard Data**

Route(s) of Entry	Eyes?	Inhalation?	Skin?	Ingestion?
	Yes	Yes	Yes	Yes (aspiration)

**Health Hazards (Acute and Chronic):** Warning: Flammable liquid and vapor. Causes eye and skin irritation. May be harmful if inhaled or swallowed. Repeated or prolonged skin contact may cause drying and defatting of skin (dermatitis). Contains petroleum distillates. Aspiration hazard if swallowed. Can cause central nervous system effects if improperly used. Use good chemical hygiene practices to avoid these hazards.

<b>Carcinogenicity:</b> Methylene Chloride	<b>NTP?</b> Yes	<b>IARC Monographs?</b> Group 2B	<b>OSHA Regulated?</b> No
-----------------------------------------------	--------------------	-------------------------------------	------------------------------

**WARNING:** This product contains a chemical (methylene chloride) known to the State of California to cause cancer.

**Signs and Symptoms of Exposure -** Burning, tearing, redness in eyes. Dryness, cracking, burning on skin. Irritation of nose, throat and digestive tract. Nausea, vomiting, drowsiness, dizziness, loss of coordination.

**Medical Conditions Generally Aggravated by Exposure -** Pre-existing lung, liver, and skin disorders may be aggravated if subjected to prolonged or repeated occupational overexposures.

**Emergency and First Aid Procedures:**

**Eyes -** Flush with plenty of water for at least 15 minutes lifting eyelids to insure complete removal. Get immediate medical attention. **Ingestion -** Seek immediate emergency medical attention. Aspiration hazard. Only induce vomiting with a physician's direction. **Inhalation -** Get to fresh air. If breathing has stopped, qualified personnel should administer artificial respiration. **Skin -** Wash thoroughly with soap and water. If irritation arises and persists, contact a physician.

**SECTION VII - Precautions for Safe Handling and Use**

**Steps to be Taken in Case Material is Released or Spilled -** Isolate traffic and ventilate area. Eliminate all ignition sources. Wear protective gear as necessary. Dike to prevent spread. Vacuum or pick up on absorbent. Caution, slip hazard. Put in a suitable container.

**Waste Disposal Method -** Consult local, state and federal regulations. Do not puncture or incinerate container. Replace cap on empty can, wrap, then discard container if allowed by applicable statutes.

**Precautions to be Taken in Handling and Storing -** Do not use around ignition sources such as heat sparks and open flame. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Remove and wash contaminated clothing before reuse. Avoid inhaling mist or vapors. Use with adequate ventilation. Do not swallow.

**Other Precautions -** Follow label directions carefully. Keep out of reach of children. Store in a cool (under 120 F) dry location away from heat, sparks, open flame, and direct sunlight. Direct spray away from face. Replace cap when not in use. Do not deliberately concentrate and inhale vapors. Do not smoke while using.

**SECTION VIII - Control Measures**

**Respiratory Protection (Specify Type) -** Not usually necessary. Use with adequate ventilation. If PELs or TLVs are exceeded (see Section II), use an approved NIOSH/MSHA respirator.

Ventilation	Local Exhaust	Not necessary	Special - None
	Mechanical (General)	Yes	Other - None

**Protective Gloves -**

Yes. If contact possible, wear impervious.

**Eye Protection -**

Yes, approved safety glasses or goggles (ANSI Z87)

**Other Protective Clothing or Equipment -** Not usually necessary. When necessary, use apron, boots, etc.

**Work/Hygienic Practices -** Normal. Wash thoroughly before eating, drinking, smoking, using restrooms, etc.

WARNING: The use of this product is beyond the control of the manufacturer; therefore, no guarantee, expressed or implied, is made as to the effects of such use or the results to be obtained if not used in accordance with directions or established safe practices. The user shall assume all responsibility, including injury or damage resulting from use as such, or in combination with other materials. The manufacturer warrants only that this product meets the manufacturer's specified use for such product. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, AS TO DESCRIPTION, QUALITY, MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, PRODUCTIVITY, OR ANY OTHER MATTER, OF THIS PRODUCT. THE MANUFACTURER SHALL BE IN NO WAY RESPONSIBLE FOR THE PROPER USE OF THIS PRODUCT. The user and others are hereby advised that the manufacturer's liability for breach of warranty shall be reimbursement of the purchase price of the product in the amount that a reasonable condition of the product shall be found to exist. NO OTHER REMEDY (INCLUDING BUT NOT LIMITED TO INCIDENTAL OR CONSEQUENTIAL DAMAGES FOR INJURY TO PERSON OR PROPERTY OR ANY OTHER INCIDENTAL OR CONSEQUENTIAL LOSS) SHALL BE AVAILABLE.

# Material Safety Data Sheet

HMIS\*

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

HEALTH  
FLAMMABILITY

1 REACTIVITY 0  
4 PERSONAL PROTECTION B

**Identity** (As Used on Label and List)

A-104 **Jell Degreaser and Tar Remover**

*Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.*

**SECTION I**

**Manufacturer's Name**

DYMON, INC.

**Emergency Telephone Number**

1-800-535-5053

**Address (Number, Street, City, State, and ZIP Code)**

3401 KANSAS AVENUE

**Telephone Number for Information**

1-800-BUY-DYMON (1-800-289-3966)

P. O. BOX 6267

**Date Prepared**

April 5, 1995

KANSAS CITY, KANSAS 66106

**Signature of Preparer (Optional)**

REGULATORY DEPT.

**SECTION II - Hazardous Ingredients/Identity Information**

Hazardous Components (Specific Chemical Identity, Common Name(s))	CAS No.	OSHA PEL	ACGIH-TLV	Other Limits	
				Recommended	%(Opt.)
*Toluene	108-88-3	100 ppm	100 ppm	150 ppm-STEL	20 - 30
Kerosene-	8008-20-6	5 mg/m <sup>3</sup> (mist)	5mg/m <sup>3</sup> (mist)		
Mineral Spirits	64742-88-7	100 ppm	100 ppm		
Propane-	74-98-6	1000 ppm	Asphyxiant		

\* This product contains Toluene which is listed and may require reporting under SARA Title III Sec. 313 if used over the threshold reporting quantity. This information must be included in all MSDSs that are copied and distributed for this material.

Any substance listed as hazardous by the States of California, Florida, Illinois, Michigan, New Jersey, Ohio, Pennsylvania or Texas is described above if known present in regulated concentrations.

**SECTION III Physical/Chemical Characteristics**

<b>Boiling Point</b> Concentrate (initial)	230° F	<b>Specific Gravity (H<sub>2</sub>O = 1)</b> Concentrate	0.83
<b>Pressure (psig. @ 70° F)</b>	35 ± 5	<b>Melting Point</b>	No Data
<b>Vapor Density (AIR = 1)</b>	Greater than one (1)	<b>Evaporation Rate (Butyl Acetate = 1)</b>	No Data
<b>Solubility in Water</b>	Emulsifiable	<b>pH</b>	Not Applicable

**Appearance and Odor**

Tan translucent jell with a petroleum odor in an aerosol can.

**SECTION IV - Fire and Explosion Hazard Data**

<b>USA Flame Projection Test (ASTM D-3065)</b> >24", Flashback; Extremely Flammable	<b>Flammable Limits</b>	No Data	<b>LEL</b> No Data	<b>UEL</b> No Data
----------------------------------------------------------------------------------------	-------------------------	---------	-----------------------	-----------------------

**Extinguishing Media -**

Carbon dioxide, dry chemical, foam, halon or water spray.

**Special Fire Fighting Procedures -** Use water spray to keep containers cool and vapors down. Do not allow runoff to enter sewers or public watercourses. Wear self-contained breathing apparatus in chemical fires.

**Unusual Fire and Explosion Hazards -**

Aerosol container (pressurized) may burst if heated over 120° F. Flammable contents.

**SECTION V - Reactivity Data**

Stability	Unstable		Conditions to Avoid - Extreme heat, direct sunlight
	Stable	X	

**Incompatibility (Materials to Avoid) -**

Strong acids, bases or oxidizing agents and selected amines.

**Hazardous Decomposition or Byproducts -**

Oxides of carbon and various hydrocarbons.

Hazardous Polymerization	May Occur		Conditions to Avoid - None known
	Will Not Occur	X	

**SECTION VI - Health Hazard Data**

Route(s) of Entry	Eyes?	Inhalation?		Skin?		Ingestion?	
		Yes	Yes	Yes	Yes		

**Health Hazards (Acute and Chronic) -** Danger. Extremely flammable. Contains petroleum distillates. Harmful or fatal if swallowed. Aspiration hazard if swallowed. May be harmful if inhaled. Causes severe eye irritation. May cause skin irritation. Overexposure to concentrated vapors may cause CNS effects. Follow good chemical hygiene practices to avoid these hazards.

<b>Carcinogenicity:</b>	<b>NTP?</b>	<b>IARC Monographs?</b>	<b>OSHA Regulated?</b>
None known	No	No	No

**WARNING:** This product contains a chemical (Toluene) known to the State of California to cause birth defects or other reproductive harm.

**Signs and Symptoms of Exposure -**

Redness, tearing and burning in eyes. Redness, drying and cracking of skin. Dizziness, drowsiness and loss of coordination if over inhaled. Gastrointestinal irritation if swallowed.

**Medical Conditions Generally Aggravated by Exposure -**

Pre-existing lung and skin disorders.

**Emergency and First Aid Procedures:**

**Eyes** - Flush with plenty of water for at least 15 minutes lifting eyelids to insure complete removal. Get immediate medical attention. **Ingestion** - Do not induce vomiting. Contact a physician or poison control center immediately. **Inhalation** - Get to fresh air. If breathing has stopped, qualified personnel should administer artificial respiration. **Skin** - Wash with soap and water. If irritation arises and persists consult a physician.

**SECTION VII - Precautions for Safe Handling and Use**

**Steps to be Taken in Case Material is Released or Spilled -** Caution. Slip hazard. For large spills, isolate traffic and ventilate area. Eliminate all ignition sources. Wear protective gear as necessary. Dike to prevent spread. Pick up on absorbent material and put in suitable container for proper disposal. Remove residues with water.

**Waste Disposal Method -** Consult local, state and federal regulations. Do not puncture or incinerate container. Replace cap on empty can, wrap, then discard container if allowed by applicable statutes.

**Precautions to be Taken in Handling and Storing -** Do not get in eyes. Avoid contact with skin and clothing. Avoid inhaling mist or vapors. Do not swallow. Wash thoroughly after handling. Store in a cool (under 120° F) dry location away from heat, sparks, open flame, and direct sunlight. Direct spray away from face. Replace cap when not in use. Do not use around ignition sources such as heat, sparks, open flame, etc.

**Other Precautions -** Follow label directions carefully. Keep out of reach of children. Do not deliberately concentrate and inhale vapors.

**SECTION VIII - Control Measures**

**Respiratory Protection (Specify Type) -** Not usually necessary. Use with adequate ventilation. If PELs or TLVs are exceeded (see Section II), use an approved NIOSH/MSHA respirator.

Ventilation	Local Exhaust	Not necessary	Special	None
	Mechanical (General)	Acceptable	Other	None

**Protective Gloves -**

Yes, impervious.

**Eye Protection -**

Yes, safety glasses or goggles (ANSI Z87).

**Other Protective Clothing or Equipment -**

As needed to avoid direct contact with skin and clothing (i.e. apron, boots, etc.).

**Work/Hygienic Practices -**

Normal. Wash thoroughly before eating, drinking, smoking, using restrooms, etc.

WARNING: The use of this product is beyond the control of the manufacturer, distributor, or government, expressed or implied, as to the effects of such use or the results to be obtained if not used in accordance with directions or established safe practices. The user must assume all responsibility, including injury or damage resulting from this use or from its combination with other materials. The manufacturer warrants only that this product meets the manufacturer's specifications for each product. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, AS TO MERCHANTABILITY, QUALITY, MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, PRODUCTIVENESS, OR ANY OTHER MATTER, OF THIS PRODUCT. THE MANUFACTURER SHALL BE IN NO WAY RESPONSIBLE FOR THE PROPER USE OF THIS PRODUCT. The user and its dealer remedy against the manufacturer for breach of warranty shall be reimbursement of the purchase price of the product in the event that a defective condition of the product shall be found to exist. NO OTHER REMEDY (INCLUDING BUT NOT LIMITED TO INCIDENTAL OR CONSEQUENTIAL DAMAGES FOR INJURY TO PERSON OR PROPERTY OR ANY OTHER INCIDENTAL OR CONSEQUENTIAL DAMAGES) SHALL BE AVAILABLE.

# Material Safety Data Sheet

HMIS®

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

HEALTH  
FLAMMABILITY

2\* REACTIVITY 0  
0 PERSONAL PROTECTION B

<b>Identity (As Used on Label and List)</b> A - 159 Penetrating Oil & Moisture Remover	<i>Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.</i>
-------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------

<b>SECTION I</b>	
<b>Manufacturer's Name</b> DYMON, INC.	<b>Emergency Telephone Number</b> 1-800-535-5053
<b>Address (Number, Street, City, State, and ZIP Code)</b> 3401 KANSAS AVENUE	<b>Telephone Number for Information</b> 1-800-BUY-DYMON (1-800-289-3966)
P.O. BOX 6267	<b>Date Prepared</b> April 5, 1995
KANSAS CITY, KANSAS 66106	<b>Signature of Preparer (Optional)</b> REGULATORY DEPT.

<b>SECTION II - Hazardous Ingredients/Identity Information</b>					
<b>Hazardous Components (Specific Chemical Identity, Common Name(s))</b>	<b>CAS No.</b>	<b>OSHA PEL</b>	<b>ACGIH-TLV</b>	<b>Other Limits Recommended</b>	<b>%(Opt.)</b>
*Perchloroethylene	127-18-4	25 ppm	50 ppm	STEL-200 ppm	60-85
Carbon dioxide	124-38-9	10000 ppm	5000 ppm	STEL-30,000 ppm	
Petroleum oil	Mixture	5 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>	STEL-10 mg/m <sup>3</sup>	
*2-Butoxyethanol (skin designation)	111-76-2	25 ppm	25 ppm		1 - 3

\* This product contains perchloroethylene (syn. tetrachloroethylene) which is listed and may require reporting under SARA Title III Sec. 313 if used over the threshold reporting quantity. This information must be included in all MSDSs that are copied and distributed for this material.

Any substance listed as hazardous by the States of California, Florida, Illinois, Michigan, New Jersey, Ohio, Pennsylvania or Texas is described above if known present in regulated concentrations.

<b>SECTION III Physical/Chemical Characteristics</b>			
<b>Boiling Point</b> Concentrate - Initial	250° F	<b>Specific Gravity (H<sub>2</sub>O = 1)</b> Concentrate	1.54
<b>Pressure (psig. @ 70° F)</b>	60 ± 5	<b>Melting Point</b>	No Data
<b>Vapor Density (AIR = 1)</b>	Greater than one (1)	<b>Evaporation Rate (Butyl Acetate = 1)</b>	No Data
<b>Solubility in Water</b>	Insoluble	<b>pH</b>	Not Applicable

**Appearance and Odor**  
Clear amber liquid with a chlorinated solvent/wintergreen scent in an aerosol container.

<b>SECTION IV - Fire and Explosion Hazard Data</b>			
<b>USA Flame Projection Test (ASTM D-3065)</b> 4", No flashback, non-flammable	<b>Flammable Limits</b> No Data	<b>LEL</b> No Data	<b>UEL</b> No Data

**Extinguishing Media**  
Not usually necessary as this product does not readily support combustion. Use extinguishing agent appropriate for fire's fuel source (i.e. carbon dioxide, dry chemical, foam, fog, etc.).

**Special Fire Fighting Procedures** - Use water spray to keep containers cool and vapors down. Do not allow runoff to enter sewers or public watercourses. Wear self-contained breathing apparatus in chemical fires.

**Unusual Fire and Explosion Hazards** -  
Aerosol container (pressurized) may burst if heated over 120° F.

SECTION V - Reactivity Data			
Stability	Unstable		Conditions to Avoid - Extreme heat, direct sunlight
	Stable	X	
Incompatibility (Materials to Avoid) - Strong oxidizers, acids and alkalis, and alkali metals.			
Hazardous Decomposition or Byproducts - Carbon dioxide, carbon monoxide, sulfur oxides, aldehydes, phosgene, hydrogen chloride, chlorine, soot and smoke.			
Hazardous Polymerization	May Occur		Conditions to Avoid - None known
	Will Not Occur	X	

SECTION VI - Health Hazard Data				
Route(s) of Entry	Eyes?	Inhalation?	Skin?	Ingestion?
	Yes	Yes	Yes	Yes
Health Hazards (Acute and Chronic) - Warning. Causes eye and skin irritation. Harmful if inhaled or swallowed. May be absorbed through intact skin. Aspiration hazard if ingested. May produce conjunctivitis with direct eye contact. Central nervous system effects possible. Follow good chemical hygiene practices to avoid these hazards.				
Carcinogenicity: Yes, perchloroethylene	NTP? Yes	IARC Monographs? Yes (Group 2B)	OSHA Regulated? Yes	
WARNING: This product contains a chemical (tetrachloroethylene) known to the State of California to cause cancer.				
Signs and Symptoms of Exposure - Burning, tearing, redness in eyes. Redness, drying or cracking skin. Irritation of nose, throat and gastrointestinal tract. Drowsiness, dizziness, loss of coordination or fatigue. Anesthetic or narcotic effects possible.				
Medical Conditions Generally Aggravated by Exposure - Pre-existing skin, lung, heart, liver or kidney disorders may be aggravated by prolonged or repeated occupational overexposures.				
Emergency and First Aid Procedures: - Eyes - Flush with plenty of water for at least 15 minutes lifting eyelids to insure complete removal. Get immediate medical attention. Ingestion - Do not induce vomiting unless under the direction of a physician. Get immediate emergency medical attention. Inhalation - Get to fresh air. If breathing has stopped, qualified personnel should administer artificial respiration. Skin - Wash thoroughly with soap and water. If irritation arises and persists, call a physician.				

SECTION VII - Precautions for Safe Handling and Use
Steps to be Taken in Case Material is Released or Spilled - Caution, slip hazard. Wipe up small spills with an absorbent material. For large spills, isolate traffic and ventilate area. Eliminate all ignition sources. Wear protective gear as necessary. Dike to prevent spread. Pick up with an absorbent material and put in suitable container for proper disposal. To eliminate slip hazard, carefully remove residuals with a suitable detergent or safety solvent.
Waste Disposal Method - Consult local, state and federal regulations. Do not puncture or incinerate container. Replace cap on empty can, wrap, then discard container if allowed by applicable statutes.
Precautions to be Taken in Handling and Storing - Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Do not swallow. Avoid inhaling mist and vapors. Store in a cool (under 120° F) dry location away from heat, sparks, open flame, and direct sunlight. Direct spray away from face. Do not puncture container.
Other Precautions - Follow label directions carefully. Keep out of reach of children. Do not deliberately concentrate and inhale vapors. Replace cap when not in use. Do not use around ignition sources such as heat, sparks, open flame, etc.

SECTION VIII - Control Measures				
Respiratory Protection (Specify Type) - Not usually necessary. Use with adequate ventilation. If PELs or TLVs are exceeded (see Section II), use an approved NIOSH/MSHA respirator.				
Ventilation	Local Exhaust	Not usually needed	Special	None
	Mechanical (General)	Acceptable	Other	None
Protective Gloves - Yes, when contact is possible.	Eye Protection - Yes, approved safety glasses or goggles (ANSI Z87).			
Other Protective Clothing or Equipment - Only when direct contact is possible. Use appropriate gear such as apron, boots, face shield, etc. when necessary.				
Work/Hygienic Practices - Normal. Wash thoroughly before eating, drinking, smoking, using restrooms, etc.				

WARNING: The use of this product is beyond the control of the manufacturer; therefore, no guarantee, expressed or implied, is made as to the safety of such use or the results to be obtained if use is in accordance with directions or established use practices. The user must assume all responsibility, including injury or damage, resulting from its use as well as its combination with other materials. The manufacturer warrants only that this product meets the normal solvent's specifications for such products. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, AS TO DESCRIPTION, QUALITY, MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, PRODUCTIVENESS, OR ANY OTHER MATTER, OF THIS PRODUCT. THE MANUFACTURER SHALL BE IN NO WAY RESPONSIBLE FOR THE PROPER USE OF THIS PRODUCT. The user and its clients remain solely responsible for the normal solvent's use or for any breach of warranty shall be the responsibility of the purchaser or the user. In the event that a defective condition of the product shall be found, NO OTHER REMEDY (INCLUDING BUT NOT LIMITED TO INCIDENTAL OR CONSEQUENTIAL DAMAGES FOR INJURY TO PERSON OR PROPERTY OR ANY OTHER INCIDENTAL OR CONSEQUENTIAL LOSS) SHALL BE AVAILABLE.